

Fire Service Connections

A fire service pumper connection, located outside buildings, permits the fire service to pump water into a sprinkler system from a nearby public hydrant or reservoir. Water supplied at high pressure will aid automatic sprinklers to control a fire. The connection may also be used to supply building standpipes.

FM Approved connections are made of bronze and consist of two inlet couplings threaded for standard fire hose and siamesed into an outlet pipe connection. A check valve is provided in each inlet so that either connection may be used separately. The connections are available in straight, 45° or 90° patterns. Unless otherwise noted in the listing, these connections have 175 psi (1205 kPa) rated working pressure.

Fig. Nos. A95, A96, A105, A106

Product Specification

Model No	Description	Nominal Size, Inlets x Outlet, in
A95	Straightway Siamese	2 1/2 x 2 1/2 x 4
A96	90° Siamese	2 1/2 x 2 1/2 x 4
A105	Straightway Siamese	2 1/2 x 2 1/2 x 4
A106	90° Siamese	2 1/2 x 2 1/2 x 4

Connections A95 & A96 are rated 300 psi (2068 kPa)

Company Name:	Giacomini SpA
Company Address:	Via per Alzo 39, 28017 San Maurizio d'Opaglio (NO) Italy
Company Website:	http://giacomini.com
New/Updated Product Listing:	No
Listing Country:	Italy
Certification Type:	FM Approved
Class of Work:	1530-Fire Department Connections