



VNIV.EX28360 - Sprinklers, Automatic and Open

Sprinklers, Automatic and Open

[See General Information for Sprinklers, Automatic and Open](#)

GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.

EX28360

ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1

SOKAK NO 4. MERMERCILER CAD

34953 TUZLA ISTANBUL, TURKEY

Sprinkler Identification Number (SIN) UV310, UV311, UV320, UV321, UV410, UV411, UV420, UV421, UV820, UV821 Glass Bulb Type.

UPRIGHT AND PENDENT STANDARD-SPRAY SPRINKLERS NOMINAL 5.6 K-FACTOR

SIN	Response Type	Type	System Working Pressure, psig	Temp Rating, °F
UV310	SR	Upright	175	135, 155, 175, 200, 286
UV311	QR	Upright	175	135, 155, 175, 200, 286
UV320	SR	Pendent	175	135, 155, 175, 200, 286
UV321	QR	Pendent	175	135, 155, 175, 200, 286

NOMINAL 8.0 K-FACTOR

SIN	Response Type	Type	Inlet Thread NPT	System Working Pressure, psig	Temp Rating, °F
UV410	SR	Upright	3/4	175	135, 155, 175, 200
UV411	QR	Upright	3/4	175	135, 155, 175, 200, 286
UV420	SR	Pendent	3/4	175	135, 155, 175, 200
UV421	QR	Pendent	3/4	175	135, 155, 175, 200, 286

STANDARD SIDEWALL-SPRAY SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
UV340	SR	Horizontal	5.6	175	135, 155, 175, 200, 286
UV341	QR	Horizontal	5.6	175	135, 155, 175, 200, 286

FLUSH, RECESSED AND CONCEALED SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	Temp Rating, °F
				Cover Sprinkler

UV820	SR	Concealed Pendent	5.6	135, 165	155, 200
UV821	QR	Concealed Pendent	5.6	135, 165	155, 200

INTERMEDIATE-LEVEL SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	Temp Rating, °F
UV310	SR	Upright	5.6	135, 155, 175, 200, 286
UV311	QR	Upright	5.6	135, 155, 175, 200, 286
UV320	SR	Pendent	5.6	135, 155, 175, 200, 286
UV321	QR	Pendent	5.6	135, 155, 175, 200, 286

Last Updated on 2020-05-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"