

# Model UVD.2511-300

## Product Specification

Model No	Valve Size		Rated Working Pressure		End Connection	Remarks
	in	(mm)	psi	(kPa)		
UVD.2511-300	3, 4, 6, 8	(80, 100, 150, 200)	300	(2065)	Flanged x Flanged	a, b, c, d

### Remarks:

- a. Approved for vertical installation only
- b. Approved when supplied with a main control valve body ASTM A536 ductile iron
- c. Approved when supplied with FM Approved pressure gauges
- d. Approved when supplied with one or more of the following optional components: dry accelerator assembly, FM Approved pressure switch and FM Approved water motor gong.

## Details

**Class of Work :** 1021 - Dry Pipe Valves  
**Approval Standard :** FM 1021 - Dry Pipe Valves  
**Certification Type :** FM Approved  
**Listing Country :** Turkiye  
**Category :** Dry Pipe System Valves

## Company

**GIACOMINI UNIVAL TESISAT ARMATÜRLERİ**  
SANAYİ VE TİCARET LTD. STİ., İstanbul Anadolu  
Yakası Organize Sanayi Bölgesi, Aydınli  
Mah.Mermerciler Cad. No: 10, Tuzla-Istanbul,  
Turkiye  
Turkiye



Cookies help us improve your website experience.  
By using our website, you agree to our use of cookies.

**Confirm**

