



Valves | Indicating Valves (Butterfly or Valve Type) | **Indicating Valves, Butterfly or Ball Type**

## Models UVB-G310, UVB-G300, UVB-W300, UVB-G and UVB-W

### Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
UVB-G310	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6	(65, 80, 100, 125, 150)	300	(2065)	a, b, c
UVB-G300	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
UVB-W300	Butterfly Valve, Wafer Body	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
UVB-G	Butterfly Valve, Grooved Ends	10	(250)	175	(1205)	a, b, c
UVB-W	Butterfly Valve, Wafer Body	10	(250)	175	(1205)	a, b, c

#### Remarks:

- Available with dual supervisory switches.
- FM Approved for indoor and outdoor use.
- FM Approved for aboveground installations only.
- FM Approved indoor service only.
- These valves cannot be installed between the fire protection system water source and sprinkler heads. Intended for use in fire pump test bypass lines only.

## Details

<b>Category</b>	Indicating Valves, Butterfly or Ball Type
<b>Class of Work</b>	1112 - Indicating Valves
<b>Approval Standard</b>	FM 1112 - Indicating Valves (Butterfly or Ball Type)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	Turkiye

## Company

**GIACOMINI UNIVAL TESISAT ARMATÜRLERİ**  
 SANAYİ VE TİCARET LTD. STİ.,  
 İstanbul Anadolu Yakası Organize Sanayi Bölgesi, Aydınli Mah. Mermerciler Cad. No: 10, Tuzla-İstanbul, Türkiye