

Valves | Indicating Valves (Butterfly or Valve Type) | Indicating Valves, Butterfly or Ball Type

Models UVB-G310, UVB-G300, UVB-W300, UVB-G and UVB-W

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
UVB-G310	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6	(65, 80, 100, 125, 150)	300	(2065)	a, b, c
UVB-G300	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
UVB-W300	Butterfly Valve, Wafer Body	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
UVB-G	Butterfly Valve, Grooved Ends	10	(250)	175	(1205)	a, b, c
UVB-W	Butterfly Valve, Wafer Body	10	(250)	175	(1205)	a, b, c

Remarks:

- a. Available with dual supervisory switches.
- b. FM Approved for indoor and outdoor use.
- c. FM Approved for aboveground installations only.
- d. FM Approved indoor service only.
- e. These valves cannot be installed between the fire protection system water source and sprinkler heads. Intended for use in fire pump test bypass lines only.

Details

Category	Indicating Valves, Butterfly or Ball Type
Class of Work	1112 - Indicating Valves
Approval Standard	FM 1112 - Indicating Valves (Butterfly or Ball Type)
Certification Type	FM Approved

Company

GIACOMINI UNIVAL TESISAT ARMATÜRLERİ
 SANAYİ VE TİCARET LTD. STİ.,
 İstanbul Anadolu Yakası Organize Sanayi Bölgesi, Aydınli Mah. Mermerciler Cad. No: 10, Tuzla-İstanbul, Türkiye

Listing Country: Türkiye
 Cookies help us improve your website experience. By using our website, you agree to our use of cookies.

Confirm

