

Model UVPR.5311-300

File Number: EX28359

COMPANY
GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.
ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1
Sokak No 4. MERMERCILER CAD
Tuzla Istanbul, Istanbul 34953 Turkiye

MODEL INFO
UVPR.5311-300

GENERAL

Sprinkler System Type	Body Type	Nominal Pipe Size, NPS	End Configuration	Max Rated Pressure, psig (kPa)	Trim Configuration Type	Installed Position
Preaction sprinkler system	Globe	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	Flanged, Grooved, Flanged by Grooved	300 (2068)	Single interlock w/ pneumatic actuation, Double interlock w/ pneumatic-pneumatic actuation	Vertical, Horizontal

GENERAL

Installation Limitations

End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

For accessories used with these valves, see certifications under Accessories for Special Systems (VLTR).

All trim configuration types shall include a manual release. Height of pilot line above valve limited as shown in the installation instructions.

Report Date: 2022-10-20
Revision Date: 2024-04-15