

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Fig. F0211-300, F0222-300, F0213-300, F0233-300, F0212-300, F0218-300, F0288-300

Resilient Seated Gate Valve. Available with an indicator post flange. Rated Working Pressure 300 psi (2070 kPa). Available with the end connections listed below:

### Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
Fig. F0211-300	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	Flange x Flange (ANSI, ISO, JIS)
Fig. F0222-300	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	Groove x Groove (ANSI, ISO, JIS)
Fig. F0213-300	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	Flange x Mechanical Joint
Fig. F0233-300	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	Mechanical Joint
Fig. F0212-300	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	Flange x Groove (ANSI, ISO, JIS)
Fig. F0218-300	4, 5, 6, 8, 10, 12	(100, 125, 150, 200, 250, 300)	Flange (ANSI, ISO, JIS) x Push-On
Fig. F0288-300	4, 5, 6, 8, 10, 12	(100, 125, 150, 200, 250, 300)	Push-On x Push-On

<b>Company Name:</b>	Weflo Valve Co., Ltd
<b>Company Address:</b>	Intersection of Huadong Road and Chunyang Road, National High-Tech Industrial Development Zone, Qingdao, P.R. China 266111
<b>Company Website:</b>	<a href="http://weflovalve.com">http://weflovalve.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	China
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	1130-OS&Y and NRS Gate Valves