



Valves | Automatic Water Control Valves | **Valves, Water Pressure Reducing**

# Figure 1320-300

## Product Description

Valve Size		End Connection	Rated Working Pressure		Flow Range		Outlet Pressure Range		Remarks
in	(mm)		psi	(kPa)	gpm	(m <sup>3</sup> /hr)	psi	(kPa)	
2	(50)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	40-200	(9-45)	65-165	(450-1140)	a, b, c, d
2 1/2	(65)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	50-250	(11-57)	65-165	(450-1140)	a, b, c, d
3	(80)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	80-400	(18-91)	65-165	(450-1140)	a, b, c, d
4	(100)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	150-750	(34-170)	65-165	(450-1140)	a, b, c, d
5	(125)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	215-1130	(49-257)	65-165	(450-1140)	a, b, c, e
6	(150)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	279-1395	(63-317)	65-165	(450-1140)	a, b, c, e
8	(200)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	497-1500	(113-341)	65-165	(450-1140)	a, b, c, e
10	(250)	Grooved x Grooved Flanged x Flanged Grooved x Flanged	300	(2065)	855-4275	(194-971)	65-165	(450-1140)	a, b, c, e

**Remarks:**

- a. Must be installed with an FM Approved pressure relief valve size ½ inch or larger
- b. Approved when supplied with a main control valve body in ASTM A536 ductile iron
- c. Approved when supplied with a pilot valve body in ASTM B148 nickel aluminum bronze C95800 or SS304 stainless steel
- d. Must maintain a 10 psi (69 kPa) or greater differential between inlet and outlet pressures for proper operation
- e. Must maintain a 15 psi (103 kPa) or greater differential between inlet and outlet pressures for proper operation

## Details

<b>Category</b>	Valves, Water Pressure Reducing
-----------------	---------------------------------

## Company

**Weflo Valve Co., Ltd**  
 789 Chunyang Rd, Qingdao Nat'l High-Tech Ind Dev Zone, Qingdao, Shandong 266111, China

# FM Approvals

<b>Class of Work</b>	1362 - Water Pressure Reduc Valves
<b>Approval Standard</b>	FM 1362 - Pressure Reducing Valves
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	China

<http://weflovalve.com>