UL Product iQ®



VPZV.EX28865 - Valves, Dry Pipe

Valves, Dry Pipe

GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.

EX28865

ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1 Sokak No 4. MERMERCILER CAD Tuzla Istanbul, 34953 Turkey

Model	Body Type	Nom Pipe Size, NPS	End Configuration*	Max Rated Pressure, psig	Installation Position
Dry-pipe valve					
UVD.2511-300	Globe	3,4, 6, 8	F by F	300	V

- F Flanged
- G Grooved
- V Vertical orientation
- * End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

Trademark and/or tradename:



Last Updated on 2022-10-24

4

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."