

VNIV.EX28360 - Sprinklers, Automatic and Open

Sprinklers, Automatic and Open

See General Information for Sprinklers, Automatic and Open

GIACOMINI UNIVAL TESISAT ARMATURLERI SANAYI VE TICARET LTD.STI.

EX28360

ISTANBUL ANADOLU TAKASI ORGANIZE SANAYI BOLGESI 1

SOKAK NO 4. MERMERCILER CAD

34953 TUZLA ISTANBUL, TURKEY

Sprinkler Identification Number (SIN) UV310, UV311, UV320, UV321, UV410, UV411, UV420, UV421, UV820, UV821 Glass Bulb Type.

UPRIGHT AND PENDENT STANDARD-SPRAY SPRINKLERS NOMINAL 5.6 K-FACTOR

| SIN | Response Type | Type | System Working Pressure, psig | Temp Rating, °F |
|-------|---------------|---------|-------------------------------|-------------------------|
| UV310 | SR | Upright | 175 | 135, 155, 175, 200, 286 |
| UV311 | QR | Upright | 175 | 135, 155, 175, 200, 286 |
| UV320 | SR | Pendent | 175 | 135, 155, 175, 200, 286 |
| UV321 | QR | Pendent | 175 | 135, 155, 175, 200, 286 |

NOMINAL 8.0 K-FACTOR

| SIN | Response Type | Type | Inlet Thread NPT | System Working Pressure, psig | Temp Rating, °F |
|-------|---------------|---------|------------------|-------------------------------|-------------------------|
| UV410 | SR | Upright | 3/4 | 175 | 135, 155, 175, 200 |
| UV411 | QR | Upright | 3/4 | 175 | 135, 155, 175, 200, 286 |
| UV420 | SR | Pendent | 3/4 | 175 | 135, 155, 175, 200 |
| UV421 | QR | Pendent | 3/4 | 175 | 135, 155, 175, 200, 286 |

STANDARD SIDEWALL-SPRAY SPRINKLERS

| SIN | Response Type | Type | Nom K-Factor | System Working Pressure, psig | Temp Rating, °F |
|-------|---------------|------------|--------------|-------------------------------|-------------------------|
| UV340 | SR | Horizontal | 5.6 | 175 | 135, 155, 175, 200, 286 |
| UV341 | QR | Horizontal | 5.6 | 175 | 135, 155, 175, 200, 286 |

FLUSH, RECESSED AND CONCEALED SPRINKLERS

| SIN | Response Type | Type | Nom K-Factor | Temp Rating, °F |
|-----|---------------|------|--------------|-----------------|
| | | | | Cover Sprinkler |

| | | | | | |
|-------|----|-------------------|-----|----------|----------|
| UV820 | SR | Concealed Pendent | 5.6 | 135, 165 | 155, 200 |
| UV821 | QR | Concealed Pendent | 5.6 | 135, 165 | 155, 200 |

INTERMEDIATE-LEVEL SPRINKLERS

| SIN | Response Type | Type | Nom K-Factor | Temp Rating, °F |
|-------|---------------|---------|--------------|-------------------------|
| UV310 | SR | Upright | 5.6 | 135, 155, 175, 200, 286 |
| UV311 | QR | Upright | 5.6 | 135, 155, 175, 200, 286 |
| UV320 | SR | Pendent | 5.6 | 135, 155, 175, 200, 286 |
| UV321 | QR | Pendent | 5.6 | 135, 155, 175, 200, 286 |

Last Updated on 2020-05-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"